



Ovation F-915VW

A high-power, variable white Fresnel-style fixture utilizing a 6-color LED system to project a bright, soft field of high-CRI light with motorized zoom and adjustable color temperature.

Ideal for theatre and TV studio applications requiring a beautifully soft field of light with superior color rendering and precise temperature control.

- Features a 6-color engine with +/- green adjustment for precise on-camera color control.
- Provides a versatile motorized zoom range of 17° to 85° for flexible beam shaping.
- Achieves adjustable color temperatures from 2800 K to 8000 K with consistent output.
- Ensures smooth, high-resolution fades with 16-bit dimming and four selectable curves.
- Delivers broadcast-ready, flicker-free operation with adjustable Pulse Width Modulation (PWM).
- Offers both DMX/RDM control and on-board dials for fast, direct adjustments.

SPECIFICATIONS

Optical

Light Source: 89 LEDs (6 red, 15 orange-red, 8 green, 12 blue, 16 royal blue, 32 lime) 3 W, (960 mA), 50,000 hours life expectancy

Color Temperature (range): 2800 to 8000 K

CRI: 88-92

Beam Angle: 17° to 54°

Field Angle: 30° to 85°

Zoom Range: 17° to 85°

Lumens (30°): 4,143

Lumens (85°): 6,792

Illuminance:

Illuminance (30°): 1,748 lux @ 5 m

Illuminance (85°): 414 lux @ 5 m

Selectable PWM: 600 Hz, 1200 Hz, 2000 Hz, 4000 Hz, 6000 Hz, 25,000 Hz

Dynamic Effects

Dimmer: Electronic

Zoom: Motorized

Strobe Rate: 0 to 27 Hz

Standalone Color Mixing: Yes

Color Temperature Presets: Yes

Dim Modes: 4

Built-in Automated Programs: No

Construction / Physical

Dimensions: 22.41 x 12.59 x 10.82in (569.44 x 320 x 275 mm)

Weight: 18.6 lb (8.5 kg)

Exterior Color: Black

Housing Material: Aluminum alloy, Aluminum die-cast

Connections

Power Connection: Edison (local) plug to Seetronic Powerkon IP65

Power Input: Seetronic Powerkon IP65

Power Output: Seetronic Powerkon IP65

Data Connectors: 3- and 5-pin XLR

Cable Length (power): 5 ft (1.5 m)

Control

Control Protocol: DMX, RDM

DMX Channels: 1, 4, 6, 7, 9, 13, 16 or 19

Modes/Personalities: 8 personalities (1, 4, 6, 7, 9, 13, 16, 19)

Electrical

Input Voltage: 100 to 240 VAC, 50/60 Hz (auto-ranging)

Power Linking: 5 units @ 120 V; 8 units @ 208 V; 9 units @ 230 V

Power and Current: 271 W, 2.3 A @ 120 V, 60 Hz

Power and Current: 262 W, 1.433 A @ 208 V, 60 Hz

Power and Current: 258 W, 1.209 A @ 230 V, 50 Hz

Certifications / Qualifications

Certifications: CE, MET, FCC, UKCA

IP Rating: IP20, dry location

Temperatures:

Temperature (startup): -4 °F to 113 °F (-20 °C to 45 °C)

Temperature (operating): -22 °F to 113 °F (-30 °C to 45 °C)

Optional Accessories

Professional Clamps: CTC-50HC, CTC-50HCN
TRUE1 Style Power Extensions Cables
3-pin or 5-pin DMX Cables
Color Blending Filters: DF60X1D, DF20D
Ovation F 7.5" Barndoor V2
Ovation 8" Pole Operated Yoke

What's Included

Ovation F-915VW
Seetronic Powerkon IP65 power cable
Gel frame (7.5 in/191 mm accessories)