



Rogue Outcast 3 Spot

A compact IP65 LED moving head spot that combines a wide zoom range with a full effects package including dual color wheels, dual gobo wheels, iris, prism, and frost. Ideal for both outdoor events and indoor installations, its durable housing provides low-maintenance protection against the elements as well as particulates like fog and haze.

- Powered by a potent 300 W cool white LED with a 7044 K color temperature.
- Offers one rotating and one fixed gobo wheel for seamless morphing and dynamic visual effects.
- Create layered looks using two independent wheels with split-color and scrolling capabilities.
- Provides advanced beam shaping with an integrated iris, 5-facet prism, and frost filter.
- Features a versatile motorized zoom from a tight 4.9° beam to a wide 38.7° wash.
- Supports DMX and RDM protocols for versatile control and remote fixture management.

SPECIFICATIONS

Optical

Light Source: 1 LED (CW) 300 W, (5 A), 7044 K, 50,000 hours life expectancy

Color Temperature (at full): 7044 K

Front lens diameter: 119 mm

CRI: 70

Beam Angle: 4.9° to 33.7°

Field Angle: 5.5° to 38°

Cutoff Angle: 5.6° to 38.7°

Zoom Range: 4.9° to 38.7°

Lumens – Source: 20,000

Lumens – Output: 14,989

Illuminance:

(4.9°): 56,916 lux @ 5 m

(38.7°): 2,145 lux @ 5 m

Selectable PWM: 600 Hz, 1,200 Hz, 2,000 Hz, 4,000 Hz, 6,000 Hz, 15,000 Hz

Dynamic Effects

Pan and Tilt: 540°/270°

Pan and Tilt Ranges: 180°, 360°, 540° pan/90°, 180°, 270° tilt

Colors (1): 7 + white, split colors, continuous scroll at variable speeds

Colors (2): 7 + white, split colors, continuous scroll at variable speeds

Gobos (1): 7 + open (7 metal), rotating, interchangeable, indexing, slot-n-lock, continuous scroll at variable speeds

Gobos (2): 8 + open (8 metal), continuous scroll at variable speeds

Gobo Size: Gobo Wheel 1 (rotating); size: 25.5 mm (outside), 14.8 mm (image), 2 mm (max. thickness)

Gobo Size: Gobo Wheel 2 (static); size: 24 mm (outside), 16 mm (image), 0.6 mm (max. thickness)

Dimmer: Electronic

Shutter/Strobe: Electronic

Zoom: Motorized

Focus: Motorized

Frost: Motorized

Iris: Motorized

Prism: 5 Facets, motorized, rotating

Strobe Rate: 0 to 20 Hz

Move in Black: Yes

Construction / Physical

Dimensions: 14.41 x 9.61 x 25.16 in (366 x 244 x 639 mm)

Weight: 51 lb (23.2 kg)

Exterior Color: Black

Housing Material: High-impact flame-retardant polymer

Connections

Power Connection: Edison (local) plug to Seetronic Powerkon IP65

Power Input: Seetronic Powerkon IP65

Power Output: Seetronic Powerkon IP65

Data Connectors: 5-pin XLR

Cable Length (power): 5 ft (1.5 m)

Control

Control Protocol: DMX, RDM

DMX Channels: 20 or 25

Modes/Personalities: 2 personalities (20, 25)

Electrical

Input Voltage: 100 to 240 VAC, 50/60 Hz (auto-ranging)

Power Linking: 2 units @ 100 V; 3 units @ 120 V; 5 units @ 208 V; 6 units @ 230 V; 6 units @ 240 V

Power and Current:

Electrical Detail: 510 W, 5.13 A @ 100 V, 60 Hz

Electrical Detail 2: 506 W, 4.24 A @ 120 V, 60 Hz

Electrical Detail 3: 493 W, 2.43 A @ 208 V, 60 Hz

Electrical Detail 4: 494 W, 2.19 A @ 230 V, 50 Hz

Electrical Detail 5: 494 W, 2.12 A @ 240 V, 50 Hz

Certifications / Qualifications

Certifications: CE, MET, UKCA

IP Rating: IP65, temporary outdoor/ wet, with pressure equalizing M12 GORE valve

Temperature (Ambient): -14 °F to 113 °F (-10 °C to 45 °C)

Maximum Exterior Surface Temperature (Tc): 80° C / 176° F

Maximum Ambient Temperature (Ta): 45° C / 113° F

Noise Levels:

Idle: 24.2 dB(A) @ 1 m

Max: 33.9 dB(A) @ 1 m

Auto: 34.5 dB(A) @ 1 m

Eco: 31.0 dB(A) @ 1 m

Full: 46.9 dB(A) @ 1 m

Optional Accessories

Clamps

IP65 5 pin DMX Cables

IP65 PowerKon Extension cables

Flight Case

What's Included

Rogue Outcast 3 Spot

Seetronic Powerkon IP65 power cord

(2) Omega brackets with mounting hardware